JiffyStair™ OSHA Series

Prefabricated Industrial Stairway

The OSHA Series stairway is designed to conform to the Federal OSHA & Cal-OSHA requirements for fixed industrial stairway applications. The 10" deep treads have an adjustable rise between 7-1/4" and 8" with an angle to climb between 37° and 42°. Custom tread widths are available.

All units shipped knocked-down. Check local code requirements before ordering.

Standard step treads are made of formed diamondplate. Safety grating treads are available on request.

See JiffyTower specification sheet for matching tower dimensions.





Ladder Industries

1040 South Camino Oro Goodyear, Arizona 85338-1417 TEL (623) 932-5798 • (800) 360-6789 FAX (623) 932-5804 • (800) 359-6789 Sacramento, CA TEL (800) 544-1406 www.LadderIndustries.com





Select the best unit for your application based on the required height. Custom Sizes are Available.

CATALOG NUMBER	ADJUSTABLE HEIGHT	HORIZONTAL RUN	TREAD WIDTH	OVERALL WIDTH	EST. WEIGHT
EX 7-36			36"	41"	245 lbs.
EX 7-42	51" to 56"	58" to 55"	42"	47"	262 lbs.
EX 7-48			48"	53"	278 lbs.
EX 8-36			36"	41"	277 lbs.
EX 8-42	58" to 64"	68" to 64"	42"	47"	296 lbs.
EX 8-48			48"	53"	314 lbs.
EX 9-36			36"	41"	309 lbs.
EX 9-42	65" to 72"	77" to 73"	42"	47"	330 lbs.
EX 9-48			48"	53"	351 lbs.
EX 10-36			36"	41"	327 lbs.
EX 10-42	72" to 80"	87" to 82"	42"	47"	364 lbs.
EX 10-48			48"	53"	387 lbs.
EX 11-36			36"	41"	372 lbs.
EX 11-42	80" to 88"	97" to 91"	42"	47"	398 lbs.
EX 11-48			48"	53"	423 lbs.
EX 12-36			36"	41"	410 lbs.
EX 12-42	87" to 96"	106" to 100"	42"	47"	438 lbs.
EX 12-48			48"	53"	466 lbs.
EX 13-36			36"	41"	467 lbs.
EX 13-42	95" to 104"	116" to 109"	42"	47"	497 lbs.
EX 13-48			48"	53"	527 lbs.
EX 14-36			36"	41"	500 lbs.
EX 14-42	102" to 112"	125" to 118"	42"	47"	533 lbs.
EX 14-48			48"	53"	565 lbs.
EX 15-36			36"	41"	534 lbs.
EX 15-42	109" to 120"	135" to 127"	42"	47"	569 lbs.
EX 15-48			48"	53"	604 lbs.
EX 16-36			36"	41"	568 lbs.
EX 16-42	116" to 128"	145" to 136"	42"	47"	605 lbs.
EX 16-48			48"	53"	642 lbs.
EX 17-36			36"	41"	560 lbs.
EX 17-42	124" to 136"	154" to 145"	42"	47"	595 lbs.
EX 17-48			48"	53"	660 lbs.
EX 18-36			36"	41"	587 lbs.
EX 18-42	131" to 144"	164" to 154"	42"	47"	622 lbs.
EX 18-48			48"	53"	657 lbs.