

JiffyTower™

Use with JiffyStairs™

JiffyTower™

JiffyTowers are manufactured for use with both IBC or OSHA Series stairways. They may be used with single or multiple height access stairs. The tower guardrails and kick plates are easily installed on any two sides as required. The entire unit is shipped knocked-down. The towers are provided with the platform height specified by the user.

The standard 3-rail guardrail restricts a 12" diameter sphere. Check your local codes as the number of rails required may vary. 4" sphere restriction designs are available.

All JiffyTowers are built to match the construction and attractive appearance of the JiffyStairs and the JiffyRail.

For ample clearance, JiffyTower width must be 12" wider than the JiffyStair tread width.



CATALOG NUMBER	DECK DIMENSIONS	CLEARANCE BETWEEN POSTS	WEIGHT*
T-3642	36" x 42"	31" x 37"	360 lbs.
T-3648	36" x 48"	31" x 43"	377 lbs.
T-3654	36" x 54"	31" x 49"	394 lbs.
T-3660	36" x 60"	31" x 55"	411 lbs.
T-4242	42" x 42"	37" x 37"	377 lbs.
T-4248	42" x 48"	37" x 43"	395 lbs.
T-4254	42" x 54"	37" x 49"	407 lbs.
T-4260	42" x 60"	37" x 55"	431 lbs.
T-4848	48" x 48"	43" x 43"	406 lbs.
T-4854	48" x 54"	43" x 49"	436 lbs.
T-4860	48" x 60"	43" x 55"	456 lbs.
T-4896	48" x 96"	43" x 91"	730 lbs.
T-5454	54" x 54"	49" x 49"	455 lbs.
T-5460	54" x 60"	49" x 55"	476 lbs.
T-6060	60" x 60"	55" x 55"	499 lbs.

*Weights for 8ft. Tower

Ladder Industries

