

Rolastair™ EZ-Climb

Specifically Designed for Forward Descent

- 45° angle of climb
- 9-1/2" rise and run per step
- 9-1/2"x 24" wide steps
- 1" diameter steel tube frame
- Standard 19" extra-deep top platform
- Diamondplate steps
- 3-4-5 step units have spring loaded casters and 32" tall guardrail
- 6 step & larger units have Stepjack floor locking device with two 3-1/2" swivel casters and two 3-1/2" rigid casters
- 6 step & larger have 42" tall guardrail and knock-down base
- Large 2" diameter rubber shoes
- OSHA Safety green enamel finish
- 350 lb. capacity

Optional Features:

- Safety grating steps and platform
- 24" Deep top models available
- Stepjack on 3-4-5 step units
- Special paint colors
- Hot dip galvanized finish



STEPS	MODEL	PLATFORM HEIGHT	OVERALL HEIGHT	BASE DIMENSIONS	EST. WEIGHT
3	EZ26H3DP	28-1/2"	60-1/2"	28"W x 40"D	59 lbs.
4	EZ26H4DP	38"	70"	30"W x 50"D	72 lbs.
5	EZ26H5DP	47-1/2"	79-1/2"	31-1/2"W x 60"D	89 lbs.
6	EZ26H6DP	57"	99"	33"W x 70-1/2"D	114 lbs.
7	EZ26H7DP	66-1/2"	108-1/2"	35"W x 80-1/2"D	131 lbs.
8	EZ26H8DP	76"	118"	36"W x 90-1/2"D	148 lbs.
9	EZ26H9DP	85-1/2"	127-1/2"	36"W x 100-1/2"D	165 lbs.
10	EZ26H10DP	95"	137"	36"W x 111"D	182 lbs.

Ladder Industries

