

Stockman™ Forklift Platforms

Model FOR/FORS Specifications

- 1-1/4" dia. tube frame
- Diamondplate deck and kick plate
- 42" guardrail
- Hinged Gate
- 84" tall backguard with fine mesh screen
- Optional 66" screened backguard available for use outside of California
- Fork lift tine tubes - 3-1/2" tall x 7-1/2" wide
- Four swivel casters standard



The Stockman™ Specifications

- 30" x 20" platform size
- Diamondplate deck and kickplate
- Tine tubes on 23" centers
- 42" handrail
- Safety Chain
- 84" tall backguard with fine mesh screen
- Accepts 42" or 48" pallets
- Approximate ship weight: 220 lbs.
- Overhead fall protection attachment point

MODEL	PLATFORM SIZE	TINE TUBE CENTERS	EST. WEIGHT
FOR	30"W x 48"L	22-1/2"	210 lbs.
FORS	36"W x 48"L	28-1/2"	229 lbs.
Stockman	30"W x 20"L	23"	220 lbs.

Extended Forklift Work Platform

- 36" x 48" platform
- Diamondplate deck and kickplate
- Tine tubes on 31" centers
- Hinging Gate
- 42" handrail
- 4 swivel casters standard
- Platform heights available in 12" increments from 48" to 120"

MODEL	PLATFORM HEIGHT	EST. WEIGHT
FORS-4FT	48"	292 lbs.
FORS-5FT	60"	300 lbs.
FORS-6FT	72"	308 lbs.
FORS-7FT	84"	316 lbs.
FORS-8FT	96"	326 lbs.
FORS-9FT	108"	334 lbs.
FORS-10FT	120"	342 lbs.

Ladder Industries

